



Product Data Sheet

S5344R

S-5344R is a flammable, fast-drying, quick-setting adhesive designed to produce a strong permanent bond in the foam fabricating and decorative laminate industry. Its outstanding features include high initial tack, high green strength and long open time. It is also VOC free.

TYPICAL PROPERTIES

| | |
|-----------------|------------------|
| Color: | Clear red |
| Viscosity: | 200 cPs |
| Base: | Synthetic Rubber |
| Solvent System: | Methyl Acetate |
| Solids: | 35.62% |
| Wt./Gal: | 7.99 lbs. |
| Open Time: | 1 Hour |
| VOC content: | 0 g/L |

S-5344R should only be applied to clean, dry surfaces. Best bonds are obtained if substrates and adhesive are maintained at temperatures above 60 °F. It is important that the adhesive be applied in a smooth, uniform coat and sufficient pressure applied to insure complete contact. Product may be sprayed, brushed or rolled. Drying time and coverage per gallon will vary according to the method and rate of adhesive application and local atmospheric conditions. Cool temperatures and/or high humidity may slow drying.

Choice Adhesives

666 Redna Terrace Ste 600 2500 Carroll Avenue
Cincinnati, OH 45215 Lynchburg, VA 24501
800-330-5566 434-847-5671
www.choiceadhesivescorp.com
service@choiceadhesivescorp.com

For Industrial Use Only

IMPORTANT: The information contained herein is correct to the best of our knowledge and tests. The recommendations and suggestions contained herein are made without guarantee or representation as to results. We recommend that adequate tests be made by the purchaser to determine if a product is suitable for the intended purpose and use. Our only obligations shall be to replace or pay for any material proved defective by our laboratory within our published shelf life period. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without any other warranties expressed or implied. The suitability of these products to an intended use shall be solely up to the user.